



China Abec 7 Bearing Supplier



Motorcycle Parts 6316 Zz Distributor of SKF
NSK NTN NACHI Koyo, O&Kai Deep Groove
Ball Bearing 6300

Bearing No. 6316

6316 Bearing 2D drawings and 3D CAD models

| | |
|-------------------------------|--------------------------|
| Size | 80x170x39 mm |
| Bore Diameter | 80 mm |
| Outer Diameter | 170 mm |
| Width | 39 mm |
| d | 80 mm |
| D | 170 mm |
| B | 39 mm |
| C | 39 mm |
| r min. | 2.1 mm |
| da min. | 92 mm |
| Da max. | 158 mm |
| ra max. | 2.0 mm |
| Weight | 3.59 Kg |
| Basic dynamic load rating (C) | 123 kN |
| Basic static load rating (C0) | 86,5 kN |
| (Grease) Lubrication Speed | 3800 r/min |
| Category | Single Row Ball Bearings |
| Inventory | 0.0 |
| Manufacturer Name | NACHI |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0 |
| Product Group | B00308 |
| Enclosure | Open |
| Precision Class | ABEC 1 ISO P0 |



China Abec 7 Bearing Supplier

| | |
|---------------------------------|--|
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Internal Clearance | C0-Medium |
| Inch - Metric | Metric |
| Long Description | 80MM Bore; 170MM Outside Diameter; 39MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage |
| Other Features | Deep Groove |
| Category | Single Row Ball Bearing |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Manufacturer URL | http://www.nachiamerica.com |
| Inner Race Width | 0 Inch 0 Millimeter |
| Bore | 3.15 Inch 80 Millimeter |
| Outside Diameter | 6.693 Inch 170 Millimeter |
| Outer Race Width | 1.535 Inch 39 Millimeter |
| Bore Type | Cylindrical Bore |
| Configuration | Single Row |
| Bore Size | 80 mm |
| Width | 39 mm |
| Fillet Radius/Chamfer | 2.1 mm |
| Dynamic Load Rating | 123,000 N |
| | |



China Abec 7 Bearing Supplier

| | |
|-------------------------|-------------------|
| Static Load Rating | 86,500 N |
| Limiting Speed - Grease | 4,000 rpm |
| Limiting Speed - Oil | 4,800 rpm |
| Factor fo | 13.2 |
| Radial Clearance | 0.010 to 0.030 mm |
| da (min) | 92 mm |
| Da (max) | 158 mm |
| ra (max) | 2 mm |